

# इंटरनेट

# मानक

## Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 10992-1 (2003): Aircraft Tyres and Rims, Part 1:  
Specifications [TED 14: Aircraft and Space Vehicles]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE



भारतीय मानक  
विमान के टायर और रिम  
भाग 1 विशिष्टि  
( पहला पुनरीक्षण )

*Indian Standard*  
**AIRCRAFT TYRES AND RIMS**  
**PART 1 SPECIFICATIONS**  
( *First Revision* )

ICS 83.160.20

© BIS 2003

**BUREAU OF INDIAN STANDARDS**  
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG  
NEW DELHI 110002

NATIONAL FOREWORD

This Indian Standard ( Part 1 ) ( First Revision ) which is identical with ISO 3324-1 : 1997 'Aircraft tyres and rims — Part 1 : Specifications' issued by the International Organization for Standardization ( ISO ) was adopted by the Bureau of Indian Standards on the recommendations of the Aircraft, Space Vehicles, Air Cargo Handling and Aircraft Electrical Equipment Sectional Committee and approval of the Transport Engineering Division Council.

IS 10992 ( Part 1 ) was originally published in 1984. This revision has been prepared by adoption of ISO 3324-1. This Indian Standard which was earlier issued in three parts, has now been revised and issued in two parts by amalgamation of Part 2 with Part 3 as under:

- Part 1 Specifications
- Part 2 Test methods for tyres

The text of the International Standard has been approved as suitable for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear referring to this standard, they should be read as 'Indian Standard'.
- b) Comma ( , ) has been used as a decimal marker while in Indian Standards, the current practice is to use a point ( . ) as the decimal marker.

In this adopted draft standard reference appears to International Standard listed below for which Indian Standard also exists. The corresponding Indian Standard, which is to be substituted in its place, is given below along with its degree of equivalence for the edition indicated:

<i>International Standard</i>	<i>Corresponding Indian Standard</i>	<i>Degree of Equivalence</i>
ISO 4223-1 : 1989 Definitions of some terms used in the tyre industry — Part 1 : Pneumatic tyres	IS 10914 ( Part 1 ) : 1991 Automotive vehicles — Pneumatic tyres : Part 1 Terms, definitions and nomenclature	Technically equivalent

For BIS Certification Marking, details are available with the Bureau of Indian Standards.

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values ( revised )'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

*Indian Standard*  
**AIRCRAFT TYRES AND RIMS**  
**PART 1 SPECIFICATIONS**  
*( First Revision )*

## **1 Scope**

This part of ISO 3324 gives specifications for new and retread aircraft tyres and for aircraft rims.

## **2 Normative reference**

The following standard contains provisions which, through reference in this text, constitute provisions of this part of ISO 3324. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this part of ISO 3324 are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 4223-1:1989, *Definitions of some terms used in the tyre industry — Part 1: Pneumatic tyres.*

## **3 Definitions**

For the purposes of this part of ISO 3324, the definitions in ISO 4223-1 and the following definitions apply.

**3.1 aspect ratio (AR):** Ratio of section height to section width.

**3.2 balance mark:** Identifying red dot, located on the sidewall at the light spot of the tyre.

**3.3 chine:** Annular protuberance located around the shoulder area of the tyre, designed to deflect water.

**3.4 ply rating:** Term used to identify a given tyre with its maximum load when used in a specific type of service. It is an index of relative tyre strength.

**3.5 skid depth (mould):** Depth of the deepest tread grooves in the mould.

**3.6 venting mark:** Identification dot, other than red, located at the vents of tyres.

**3.7 retread tyre:** Tyre which has been subjected to a retreading operation.

## 4 New tyres

### 4.1 Tyre size designation

The tyre size designation for new design tyres in accordance with this part of ISO 3324 shall include a three-part size marking as follows:

Overall diameter × Overall section width - Nominal rim diameter

- tyre overall diameter and overall section width, both expressed in millimetres (mm) or both expressed in inches (in);
- nominal rim diameter, expressed as a code (see table 1).

For radial-ply tyres, the letter "R" shall be inserted between the overall section width and nominal rim diameter in the tyre size designation replacing the hyphen ("-").

The size designation may also include one of the following letter prefixes:

- B indicates tyres for 15° bead seat rims with 60 % to 70 % rim width to tyre section width ratio;
- H indicates tyres for 5° bead seat rims with 60 % to 70 % rim width to tyre section width ratio.

### 4.2 Tyre markings

The marking of new tyres shall include the following:

- a) tyre size designation;
- b) ply rating (optional);
- c) maximum speed rating expressed in knots (kn) or miles per hour (mile/h);

NOTE 1 Mile/h is also sometimes written mph.

- d) skid depth (mould) expressed in millimetres or inches;
- e) original serial number and date of manufacture: the date of manufacture shall be expressed numerically and may use a system of marking based on the Gregorian calendar (for example 12 March 1989 becomes 9071, the 9 representing 1989 and 071 representing 12 March which is the 71st day of the year) or specify month and year of manufacture with a dash ("-") separating them (for example March 1989 becomes 03-89);

NOTE 2 The numerical date of manufacture may form the first four digits of the manufacturer's unique serial number.

- f) the word "tubeless" if applicable;
- g) manufacturer's (brand) name, and country of manufacture;
- h) balance mark;
- i) venting mark if applicable;
- j) rated load (kg or lb);
- k) part number.

### 4.3 Bias tyre dimensions and growth allowances

#### 4.3.1 Tyre dimensions

New inflated tyre dimensional tolerances shall be calculated using the factors shown in figure 3 or 4. When used, the size designation as defined in 4.1 determines the maximum overall diameter and maximum section width of the new inflated tyre. Therefore tolerances shall be specified as a minus from the permitted maximum dimensions.

Tyre dimensions shall be measured after the new tyre has been mounted on the specified rim, inflated to its rated inflation pressure, and allowed to stand for a minimum of 12 h at normal room temperature and the inflation pressure readjusted to the original value. The maximum section width includes elevations due to labelling (marking, decorations, and all protective bands or ribs except chines).

#### 4.3.2 Determination of growth allowances

##### 4.3.2.1 General

Growth allowances provide for the increase in tyre dimensions over the maximum new inflated tyre dimensions to allow for growth or stretch of the tyre during service.

##### 4.3.2.2 Dimensions and symbols

The following dimensions and symbols are used (also see figure 2):

	Inflated new tyre	Inflated growth tyre
Maximum section width <sup>1)</sup>	$W$	$W_G$
Maximum shoulder width <sup>2)</sup>	$W_S$	$W_{SG}$
Maximum overall diameter	$D_o$	$D_G$
Maximum shoulder diameter	$D_S$	$D_{SG}$
Maximum section height	$H$	—
Maximum shoulder height	$H_S$	—
Aspect ratio		AR
Ply rating		PR
Specified rim diameter		$D$
Nominal rim diameter code		$D_r$
Section height growth factor		$G_H$
Section width growth factor		$G_W$
Minimum lateral distance required from wheel centreline to adjacent structure		$W_X$
Minimum radial distance required from axle centreline to adjacent structure		$R_X$
Minimum lateral clearance <sup>3)</sup>		$C_W$
Minimum radial clearance <sup>3)</sup>		$C_R$
Minimum shoulder clearance <sup>3)</sup>		$S_X$

1) Maximum section width includes protective side ribs, lettering bars and decorations, but does not include chines (water deflectors) present on certain types of nose wheel (or auxiliary gear) tyres.

2) Maximum shoulder width does not include chines (water deflectors) present on certain types of nose wheel (or auxiliary gear) tyres.

3) These are minimum clearance allowances between the maximum grown tyre and the adjacent structure.



### 4.3.2.3 Calculations

4.3.2.3.1 Determine grown dimensions as follows, using the appropriate growth factor given in 4.3.2.3.2:

$$W_G = G_W W$$

$$W_{SG} = G_W W_S$$


$$D_G = D_r + 2G_H H$$

$$D_{SG} = D_r + 2G_H H_S$$

$$H = \frac{D_o - D_r}{2}$$

$$H_s = \frac{D_s - D_r}{2}$$

4.3.2.3.2 Growth factors are expressed in figure 1.



Section width growth factor,  $G_W = 1,04$

Section height growth factor,  $G_H = 1,115 - (0,075 \times AR)$

**Figure 1 — Growth factors**

4.3.2.3.3 Obtain the new tyre dimensions  $D_o$ ,  $D_s$ ,  $W$  and  $W_s$ , as shown in the tyre tables (see annex A); such dimensions should be considered maxima.

4.3.2.3.4 The maximum shoulder width,  $W_s$ , and the maximum shoulder height,  $H_s$ , are determined by the formulae:

$$W_s = 0,9 W$$

$$H_s = 0,9 H$$

4.3.2.3.5 Nominal rim diameters are shown in table 1.

**Table 1 — Nominal rim diameter code**

Code	Nominal rim diameter, $D_r$	
	inch	mm
4	4	102
5	5	127
6	6	152
7	7	178
8	8	203
9	9	229
10	10	254
11	11	279
12	12	305
13	13	330
14	14	356
15	15	381
16	16	406
17	17	432
18	18	457
19	19	483
20	20	508
21	21	533
22	22	559
23	23	584
24	24	610

#### 4.4 Radial tyre dimensions and dimensional tolerances

The dimensions to be specified for radial tyres are the grown tyre dimensions. They include:

- a) the maximum overall diameter,  $D_G$ ;
- b) the maximum section width,  $W_G$ ;
- c) the maximum shoulder diameter,  $D_{SG}$ ;
- d) the maximum shoulder width,  $W_{SG}^{1)}$ ;

1) For some tyre sizes, the maximum shoulder width should be calculated using the formula:

$$W_{SG} = 0,88 W_G$$

Consult the tyre manufacturer for application recommendation.

- e) the minimum static loaded radius,  $SLR_{G,min}$ ;
- f) the maximum static loaded radius,  $SLR_{G,max}$ .

$D_G$ ,  $W_G$ ,  $D_{SG}$ ,  $W_{SG}$  are the maximum permitted grown inflated tyre dimensions.  $SLR_G$  is the loaded radius when the grown tyre is inflated to its rated inflation pressure, and loaded to its rated load against a flat surface.

Grown dimensions shall be measured on tyres that have completed a sufficient number of take-off cycles. Tyres shall be allowed to cool to room temperature and shall be measured at the rated inflation pressure.

The size designation defined in 4.1 determines the maximum dimensions of an equivalent new inflated bias tyre that would have the same grown dimensions as calculated in 4.3.2.

## 4.5 Determination of clearance allowances

### 4.5.1 Clearance around individual tyres

Clearance allowances between the tyre and the adjacent parts of the aircraft shall be provided by the aircraft manufacturer. These allowances are to be based on the maximum overall tyre dimensions plus growth allowances due to service, plus the increase in diameter due to centrifugal force. Minimum distances to adjacent parts of the aircraft are determined as specified in 4.5.1.1 to 4.5.1.3.

**4.5.1.1** Determine the maximum grown tyre envelope as specified in 4.3.2. for bias tyres and 4.4 for radial tyres. (This is the dotted line labelled "grown (used) inflated tyre" in figure 2.)

**4.5.1.2** Obtain the radial ( $C_R$ ) and lateral ( $C_W$ ) clearances from the formulae in a) or b) as appropriate.

For speeds which do not fall into the stated categories, clearance dimensions are to be interpolated.

a) For dimensions in millimetres:

$$C_R = 0,084 W_G + 10 \quad \text{for 230 kn (265 mile/h)}$$

$$= 0,07 W_G + 10 \quad \text{for 213 kn (245 mile/h)}$$

$$= 0,063 W_G + 10 \quad \text{for 204 kn (235 mile/h)}$$

$$= 0,06 W_G + 10 \quad \text{for 195 kn (225 mile/h)}$$

$$= 0,047 W_G + 10 \quad \text{for 182 kn (210 mile/h)}$$

$$= 0,037 W_G + 10 \quad \text{for 165 kn (190 mile/h)}$$

$$= 0,029 W_G + 10 \quad \text{for 139 kn (160 mile/h)}$$

$$= 0,023 W_G + 10 \quad \text{for 104 kn (120 mile/h)}$$

$$C_W = 0,019 W_G + 6$$

b) For dimensions in inches:

$$\begin{aligned} C_R &= 0,084 W_G + 0,4 \text{ for 230 kn (265 mile/h)} \\ &= 0,07 W_G + 0,4 \text{ for 213 kn (245 mile/h)} \\ &= 0,063 W_G + 0,4 \text{ for 204 kn (235 mile/h)} \\ &= 0,06 W_G + 0,4 \text{ for 195 kn (225 mile/h)} \\ &= 0,047 W_G + 0,4 \text{ for 182 kn (210 mile/h)} \\ &= 0,037 W_G + 0,4 \text{ for 165 kn (190 mile/h)} \\ &= 0,029 W_G + 0,4 \text{ for 139 kn (160 mile/h)} \\ &= 0,023 W_G + 0,4 \text{ for 104 kn (120 mile/h)} \end{aligned}$$

$$C_W = 0,019 W_G + 0,23$$

**4.5.1.3** Determine the distance to adjacent parts as follows:

a) The radial distance from the axle centreline to the adjacent part,  $R_{X,min}$ , is given by

$$R_{X,min} = \frac{D_G}{2} + C_R$$

b) The lateral distance from the wheel centreline to the adjacent part,  $W_{X,min}$ , is given by

$$W_{X,min} = \frac{W_G}{2} + C_W$$

c) The radius or clearance allowed between tyre shoulder area and adjacent part,  $S_{X,min}$ , is given by

$$S_{X,min} = \frac{C_W + C_R}{2}$$


NOTE — The radial clearance,  $S_{X,min}$ , includes allowances for increase in tyre diameter due to centrifugal force.

## 4.5.2 Spacing between twin tyres

The minimum distance between the tyre tread centrelines shall be  $1,18 \times W_G$ , where  $W_G$  is the maximum grown width of the tyre.

## 4.5.3 Spacing between tyres in tandem


The minimum distance between axle centres shall be  $D_G + 2C_R$ , where  $D_G$  is the maximum grown tyre diameter and  $C_R$  is the tyre radial clearance allowance for the maximum aircraft ground speed.



NOTE — Radii  $\frac{W_S}{2}$  and  $\frac{W_{SG}}{2}$  are drawn through their respective shoulder points tangent to  $D_0$  and  $D_G$  respectively. Radii below the shoulder points pass through the shoulder points and are tangent to  $W$  and  $W_G$  respectively.

Dimensions  $W$  and  $W_G$  include all protective side ribs, lettering, bars, and decorations, but do not include chines.


**Figure 2 — Grown and clearance allowances**



Percent of tolerance

Maximum section width, $W$ mm	Formula %
$0 < W \leq 127$	6
$127 < W \leq 890$	$6,5 - 0,004W$
Maximum section height, $H$ mm	
$0 < H \leq 100$	6
$100 < H \leq 355$	$7 - 0,01H$
$355 < H \leq 635$	$(1\ 335 - H)/280$
$635 < H \leq 890$	$3,75 - 0,002H$

Figure 3 — Dimensional tolerances for new aircraft tyre section height and width: millimetres



Maximum section width, $W$ in	Formula %
$0 < W \leq 5$	6
$5 < W \leq 35$	$6,5 - 0,1W$
Maximum section height, $H$ in	
$0 < H \leq 4$	6
$4 < H \leq 14$	$7 - 0,25H$
$14 < H \leq 25$	$(52,5 - H)/11$
$25 < H \leq 35$	$3,75 - 0,05H$

Figure 4 — Dimensional tolerances for new aircraft tyre section height and width: inches

## 5 Retread tyres

### 5.1 Tyre size designation

Designation is the same as the new tyre size designation, as detailed in 4.1.

### 5.2 Tyre markings

The tyre markings may be original carcass markings and/or retread markings.

The marking of retread tyres shall include the following:

- original tyre size designation;
- ply rating, if marked on original tyre;
- maximum speed rating expressed in knots or mile/h (miles per hour);
- original serial number;
- original carcass date of manufacture unless part of original serial number;

- f) the word "tubeless" if applicable;
- g) original manufacturer's (brand) name, and country of manufacture;
- h) retreader's name;
- i) retreader's factory location;
- j) date of retread: this shall be expressed numerically and may use a system based on the Gregorian calendar (for example 12 March 1989 becomes 9071, the 9 representing 1989 and 071 representing 12 March which is the 71st day of the year) or specify month and year of retreading with a dash ("–") separating them (for example March 1989 becomes 03–89);
- k) retread level: letter R located separately from the tyre size designation followed by the total number of times the tyre has been retreaded (for example, R-3);
- l) balance mark — applicable to retread tyres;
- m) skid depth (retread mould) expressed in millimetres or inches;
- n) venting marks, if applicable;
- o) rated load (kg) or (lb);
- p) retreader's designated part number which will identify the standard of the retread.

### 5.3 Retread tyre dimensions

Retread tyre dimensional tolerances shall be in accordance with the new tyre grown dimensional tolerances as detailed in 4.3 and 4.4.

## 6 Rims

### 6.1 Fundamental rim standards

#### 6.1.1 Symbols

The following symbols for dimensions are used:

- $A$  width between flanges
- $B_{\min}$  minimum flange width
- $G_{\min}$  minimum ledge width
- $F_H$  flange height
- $F_D$  flange diameter
- $I_{\min}$  minimum well depth
- $F_R$  flange radius
- $J_R$  heel radius (redesigned or recently designed rims may follow rim heel compound radius clearance envelope in figure 6)
- $r_R$  flange edge radius
- $D$  specified rim diameter at distance  $x$  from flange (see figure 9)
- $D_i$  sharp diameter (diameter at intersection of flange vertical and bead seat taper) common to both conventional and compound bead seats



$Y_R$  primary (blend) radius of compound heel contour (see figure 6) tangent to bead taper at distance  $T$  from vertical flange

$P_R$  secondary radius of compound heel contour (see figure 6) tangent to both flange vertical and  $Y_R$

$T$  horizontal distance from flange vertical to tangent of bead seat taper and  $Y_R$

$V_{min}$  valve hole location for tube-type tyre (see figure 10).

### 6.1.2 Rim dimensions

Figure 5 shows the contour of the bead seat area, where the heel radius,  $J_R$ , has the values given in tables 2 and 3. Figure 6, in conjunction with tables 2 and 3, gives the design envelope for compound heel radii of the existing series.





Figure 5 — Contour of bead seat area



Point A Tangent of  $Y_R$  to Bead Seat

Point B Intersection of  $D$  diameter with bead seat ledge

NOTE —  $Y_R$ ,  $P_R$ ,  $T$  and  $D_1$  are design dimensions. For maximum values use maximum  $J_R$  and  $D$  dimensions.

Figure 6 — Design envelope for compound heel radii

**Table 2 — Compound heel radii dimensions in millimetres**

Dimensions in millimetres

$J_R$	$T$	$P_R^{1)}$	$Y_R^{2)}$	$D_i$
1,98	3,05	1,57	3,96	$D + 0,33$
2,39	3,66	1,57	4,78	$D + 0,40$
2,77	4,24	1,57	5,54	$D + 0,46$
3,18	4,88	1,57	6,35	$D + 0,53$
3,96	6,07	1,57	7,92	$D + 0,66$
4,37	6,71	1,57	8,74	$D + 0,73$
4,75	7,29	1,57	9,50	$D + 0,79$
4,78	7,32	1,60	9,55	$D + 0,80$
5,16	7,90	1,73	10,31	$D + 0,86$
5,56	8,53	1,85	11,13	$D + 0,93$
5,59	8,56	1,85	11,18	$D + 0,94$
6,35	9,75	2,11	12,70	$D + 1,06$
7,14	10,95	2,39	14,27	$D + 1,19$
7,85	12,04	2,62	15,70	$D + 1,31$
7,92	12,17	2,64	15,85	$D + 1,33$
8,59	13,16	2,87	17,17	$D + 1,44$
8,74	13,41	2,92	17,48	$D + 1,46$
8,89	13,64	2,97	17,78	$D + 1,49$
9,30	14,25	3,10	18,59	$D + 1,56$
9,53	14,61	3,18	19,05	$D + 1,59$
10,01	15,34	3,33	20,02	$D + 1,67$
10,16	15,60	3,38	20,32	$D + 1,70$
10,72	16,43	3,58	21,44	$D + 1,79$
11,13	17,07	3,71	22,25	$D + 1,86$
11,43	17,53	3,81	22,86	$D + 1,91$
12,70	19,48	4,24	25,40	$D + 2,12$
13,97	21,44	4,65	27,94	$D + 2,34$
16,51	25,32	5,51	33,02	$D + 2,76$
1) $P_R = \frac{J_R}{3}$ , $P_R$ min. = 1,57 mm				
2) $Y_R = 2J_R$				

**Table 3 — Compound heel radii dimensions in inches**

Dimensions in inches

$J_R$	$T$	$P_R^{1)}$	$Y_R^{2)}$	$D_i$
0,078	0,120	0,062	0,156	$D + 0,013$
0,094	0,144	0,062	0,188	$D + 0,016$
0,109	0,167	0,062	0,218	$D + 0,018$
0,125	0,192	0,062	0,250	$D + 0,021$
0,156	0,239	0,062	0,312	$D + 0,026$
0,172	0,264	0,062	0,344	$D + 0,029$
0,187	0,287	0,062	0,374	$D + 0,031$
0,188	0,288	0,063	0,376	$D + 0,031$
0,203	0,311	0,068	0,406	$D + 0,034$
0,219	0,336	0,073	0,438	$D + 0,037$
0,220	0,337	0,073	0,440	$D + 0,037$
0,250	0,384	0,083	0,500	$D + 0,042$
0,281	0,431	0,094	0,562	$D + 0,047$
0,309	0,474	0,103	0,618	$D + 0,052$
0,312	0,479	0,104	0,624	$D + 0,052$
0,338	0,518	0,113	0,676	$D + 0,057$
0,344	0,528	0,115	0,688	$D + 0,058$
0,350	0,537	0,117	0,700	$D + 0,059$
0,366	0,561	0,122	0,732	$D + 0,061$
0,375	0,575	0,125	0,750	$D + 0,063$
0,394	0,604	0,131	0,788	$D + 0,066$
0,400	0,614	0,133	0,800	$D + 0,067$
0,422	0,647	0,141	0,844	$D + 0,071$
0,438	0,672	0,146	0,876	$D + 0,073$
0,450	0,690	0,150	0,900	$D + 0,075$
0,500	0,767	0,167	1,000	$D + 0,084$
0,550	0,844	0,183	1,100	$D + 0,092$
0,650	0,997	0,217	1,300	$D + 0,109$
1) $P_R = \frac{J_R}{3}$ , $P_R$ min. = 0,062 in				
2) $Y_R = 2J_R$				

#### 6.1.2.1 Rim dimensions in millimetres

For rim dimensions in millimetres, multiply the final values determined from table 4 by 25,4 and round to one less decimal place than the original rounded inch values.

### 6.1.2.2 Rim dimensions in inches

Rim dimensions of the inch series shall be as given in table 4.

**Table 4 — Rim dimensions in inches**


Wheel details	Ratio of rim width to maximum tyre – section width <sup>1)</sup>		
	60 % to 70 %		70 % and over
<b>Size designation prefix</b>	"B" prefix	"H" prefix	No prefix
<b>Bead ledge taper</b>	15°	5°	5°
<b>Nominal rim diameter (<math>D_r</math>) code<sup>2)</sup></b>	For 1 inch increments of the code, diameter to end in 5 (examples: 10.5; 12.5).	For 1 inch increments of the code, diameter to end in whole number (examples: 20; 21).	For 1 inch increments of the code, diameter to end in whole number (examples: 15; 16).
<b>Flange height, <math>F_H</math></b>	0,75 × calculated flange height (see figure 11). Round to nearest 0,125 in.	0,85 × calculated flange height (see figure 11). Round to nearest 0,05 in for flange height < 1 in, and to nearest 0,1 in for flange height ≥ 1 in.	See figure 11. Round up to nearest 0,125 in increment.
<b>Flange radius, <math>F_R</math></b>	0,67 × flange height rounded down to nearest 0,125 in.	0,6 × flange height rounded down to nearest 0,05 in.	0,5 × flange height. Round down to nearest 0,05 in.
<b>Heel radius <math>J_R</math></b>	0,33 × flange height rounded to nearest 0,05 in.	0,3 × flange height rounded up to nearest 0,05 in.	0,25 × flange height for flanges ≤ 1,25 in height and 0,225 of flange height for flanges > 1,25 in height. In all cases, round flange height to nearest 0,05 in.
<b>Minimum flange width, <math>B_{min}</math></b>	1,3 × flange radius rounded to the nearest 0,001 in.	1,3 × flange radius rounded to the nearest 0,001 in.	1,3 × flange radius rounded to the nearest 0,001 in.
<b>Rim width between flanges – Increments, (A)</b>	max. tyre width × 0,65. Round to nearest 0,25 in.		Maximum tyre width × 0,775. Round to nearest 0,25 in.
<b>Flange edge radius, <math>r_R</math></b>	0,062 in min.		
<b>Minimum well depth, <math>l_{min}</math></b>	0,268( $G_{min} - J_R$ ) + 0,002 5 $D$ . Round to nearest 0,001 in.	0,087 5( $G_{min} - J_R$ ) + 0,002 5 $D$ . Round to nearest 0,001 in.	

1) For new designs the preferred ratio of rim width to maximum tyre – section width for "B" and "H" type tyres is 65 % (adjusted to the nearest appropriate rim increment as shown above).

2) See tables 7 and 8 for specified rim diameters and tolerances.


### 6.1.3 Alternate asymmetric rim flange contours

Aircraft applications may require the use of alternate rim flange contours as shown in figures 7 and 8.



NOTE — The term “inboard” refers to the flange closest to the axle attachment point.

Figure 7 — Inboard flange height decrease from specified dimension



NOTE — The term “outboard” refers to the flange furthest from the axle attachment point.

Figure 8 — Outboard flange height increase from specified dimension

6.1.4 Rim flange height

For inch dimensions see figure 11.

6.1.5 Width between rim flanges

See table 4.

## 6.2 Inspection tolerances of rims

Inspection tolerances for the rims given in 6.1.2.1 and 6.1.2.2 shall be as given in 6.2.1 and 6.2.2 respectively.

### 6.2.1 Inspection tolerances for dimensions in millimetres

Inspection tolerances for rim dimensions of the millimetre series shall be as given in table 5.

**Table 5 — Rim inspection tolerances in millimetres**

Dimensions in millimetres

Dimension (see 6.1.1)	Tolerance	
	plus	minus
$A$	1,6	1,6
$B_{\min}$	(Minimum dimension)	
$D^{1)}$	See table 7	
$D_i$	0,05 <sup>2)</sup>	0,05 <sup>2)</sup>
$G_{\min}$	(Minimum dimension)	
$J_R$	0,25	0,25
$F_R$	0,4	0,4
$F_D$	0,5	0,5
Bead seat taper	30'	30'
1) $D$ is used as a minimum value for calculations unless otherwise stated.		
2) Add to the rim diameter tolerances given in table 7.		

### 6.2.2 Inspection tolerances for dimensions in inch

Inspection tolerances for rim dimensions of the inch series shall be as given in table 6


**Table 6 — Rim inspection tolerances in inches**

Dimensions en inches

Dimension (see 6.1.1)	Tolerance	
	plus	minus
$A$	0,063	0,063
$B_{\min}$	(Minimum dimension)	
$D^{1)}$	See table 8	
$D_i$	0,002 <sup>2)</sup>	0,002 <sup>2)</sup>
$G_{\min}$	(Minimum dimension)	
$J_R$	0,01	0,01
$F_R$	0,016	0,016
$F_D$	0,02	0,02
Bead seat taper	30'	30'
1) $D$ is used as a minimum value for calculations unless otherwise stated. 2) Add to the rim diameter tolerances given in table 8.		

### 6.2.3 Method of dimensioning and inspection tolerances for rim diameters, dimension $D$ , for rims with single heel radius

Dimensioning and inspection tolerances for rim diameters dimension,  $D$ , for rims with a single heel radius shall be in accordance with figure 9, and either table 7, for specified rim diameters in millimetres, or table 8, for specified rim diameters in inches.



For 5° rim,  $x = 0,956J_R$   
For 15° rim,  $x = 0,868J_R$

**Figure 9 — Dimensioning of  $D$  specified rim diameter**

**Table 7 — Specified rim diameters in millimetres**

Dimensions in millimetres

Nominal rim diameter ( $D_r$ ) code	Specified rim diameter		
	$D$	Tolerances on $D$	
		plus	minus
4	101,60	0,33	0,00
5	127,00	0,41	
6	152,40	0,51	
7	177,80	0,51	0,00
8	203,20	0,51	
9	228,60	0,51	
10	254,00	0,53	
11	279,40	0,53	0,00
12	304,80	0,53	
13	330,20	0,53	
14	355,60	0,53	
15	381,00	0,56	0,00
16	406,40	0,56	
17	431,80	0,56	
18	457,20	0,56	
19	482,60	0,56	0,00
20	508,00	0,61	
21	533,40	0,64	
22	558,80	0,66	
23	584,20	0,69	0,00
24	609,60	0,69	
25 and over	635,00 and over	0,71	

### 6.3 Valve, fuse plug and over pressure hole locations for connections to valve or plug hole location, $V_{min}$

#### 6.3.1 For tubeless tyres

- If valve, fuse plug, or over pressure plug hole infringes into the minimum ledge width,  $G_{min}$ , the hole shall be recessed.
- Recessed area shall be 7,5 mm (0,3 in) minimum width by 2,5 mm (0,1 in) minimum depth at  $G_{min}$ .
- Recessed area shall extend 12,5 mm (0,5 in) minimum past  $G_{min}$  or exit into well area.
- Recessed area may only extend into  $G_{min}$  dimension, 15 % of  $G_{min}$  or 12,5 mm (0,5 in) whichever is less.



Table 8 — Specified rim diameters in inches

Dimensions in inches

Nominal rim diameter ( $D_r$ ) code	Specified rim diameter		
	$D$	Tolerances on $D$	
		plus	minus
4	4,000	0,013	0,000
5	5,000	0,016	
6	6,000	0,020	
7	7,000	0,020	0,000
8	8,000	0,020	
9	9,000	0,020	
10	10,000	0,021	
11	11,000	0,021	0,000
12	12,000	0,021	
13	13,000	0,021	
14	14,000	0,021	
15	15,000	0,022	0,000
16	16,000	0,022	
17	17,000	0,022	
18	18,000	0,022	
19	19,000	0,022	0,000
20	20,000	0,024	
21	21,000	0,025	
22	22,000	0,026	
23	23,000	0,027	0,000
24	24,000	0,027	
25 and over	25,000 and over	0,028	

6.3.2 For tube-type tyres

$V_{\min} = 1,2G_{\min} + 0,1G_{\min}$  where  $0,1G_{\min}$  shall not be less than 5 mm (0,2 in) (see figure 10).





Figure 10 — Valve hole location for tube-type tyre



NOTES

- 1 Base flange height on the required PR plus 4 — to allow for increased aircraft weight.
- 2 When calculated value falls above a given curve, apply value applicable to the next higher curve.

Figure 11 — Rim flange height in inches

## Annex A (informative)

### Aircraft tyre size designations

A list of tyre size designations are given for information in table A.1. These sizes are standardized by the following national standards bodies:

TRA — The Tire and Rim Association, Inc.

ETRTO — The European Tyre and Rim Technical Organization.

#### NOTES

- 1 If the size is listed under more than one standard, there may be minor variations in the data.
- 2 This list is not restrictive. New sizes will be added as they are standardized.

**Table A.1**

Tyre size	TRA	ETRTO	Possible further standards bodies
5.00 - 4	x		
5.00 - 5	x	x	
6.00 - 6	x	x	
6.50 - 8	x	x	
6.50 - 10	x	x	
7.00 - 6	x	x	
7.00 - 8	x		
7.25 - 6		x	
7.50 - 10		x	
7.50 - 14	x	x	
8.00 - 4	x		
8.00 - 6	x		
8.00 - 7		x	
8.50 - 6	x	x	
8.50 - 10	x	x	
8.90 - 12.50	x		
9.00 - 6	x	x	
9.00 - 10		x	
9.25 - 12		x	
9.50 - 16	x	x	
10.50 - 16		x	
11.00 - 12	x	x	
12.50 - 16	x	x	
15.00 - 12	x		
15.00 - 16	x	x	
15.50 - 20	x	x	
17.00 - 16	x		
17.00 - 20	x		
20.00 - 20		x	
16 x 4.4 (-8)	x	x	
18 x 4.4 (-10)	x	x	
20 x 4.4 (-12)		x	
18 x 5.5 (-8)	x	x	
22 x 5.5 (-12)		x	
24 x 5.5 (-14)		x	
18 x 5.7 (-8)		x	
24 x 6.6 (-12)		x	
26 x 6.6 (-14)	x	x	
25 x 6.75 (-14)		x	
24 x 7.7 (-10)	x	x	

Tyre size	TRA	ETRTO	Possible further standards bodies
29 × 7.7 (-15)	x	x	
30 × 7.7 (-16)		x	
24.5 × 8.5 (-10)		x	
30 × 8.8 (-15)		x	
32 × 8.8 (-16)	x	x	
34 × 11 (-14)	x	x	
36 × 11 (-16)	x	x	
40 × 12 (-18)	x	x	
39 × 13 (-16)	x	x	
40 × 14 (-16)	x	x	
42 × 15 (-16)	x	x	
44 × 16 (-18)	x	x	
46 × 16 (-20)	x	x	
49 × 17 (-20)	x	x	
18 × 4.25 - 10	x	x	
20 × 5.25 - 11		x	
14.5 × 5.5 - 6	x	x	
17.5 × 5.75 - 8	x	x	
18 × 5.75 - 8	x		
22 × 5.75 - 12	x	x	
15 × 6.0 - 6	x		
17.5 × 6.25 - 6	x	x	
22 × 6.5 - 10	x		
18 × 6.5 - 8		x	
19.5 × 6.75 - 8	x	x	
H19.5 × 6.75 - 10	x		
22 × 6.75 - 10	x	x	
25.75 × 6.75 - 14	x		
26 × 6.75 - 14	x		
23 × 7.0 - 12	x	x	
21 × 7.25 - 10	x		
24 × 7.25 - 10		x	
24 × 7.25 - 12	x		
22 × 7.75 - 10	x		
25 × 7.75 - 10	x		
26 × 7.75 - 13		x	
27 × 7.75 - 15	x		
22 × 8.0 - 8	x		
22 × 8.0 - 10	x		
24 × 8.00 - 13		x	
25.5 × 8.0 - 14		x	
26 × 8.0 - 14		x	
H26.5 × 8.0 - 14	x		
29 × 8.00 - 15		x	
22 × 8.5 - 11		x	
C24.5 × 8.5 - 12	x		
H27 × 8.5 - 14	x		
25.5 × 8.75 - 10		x	
26 × 8.75 - 11		x	
28 × 9.0 - 12		x	
29 × 9.0 - 15	x		
30 × 9.0 - 15		x	
35 × 9.00 - 17		x	
34 × 9.25 - 16	x		
H34 × 9.25 - 18	x		
B24 × 9.5 - 10.5	x		
31 × 9.75 - 14		x	
H31 × 9.75 - 13	x		
35 × 10 - 17		x	
36 × 10 - 18		x	
31 × 10.75 - 14		x	

Tyre size	TRA	ETRTO	Possible further standards bodies
32 x 10.75 - 14		x	
33.5 x 10.75 - 15		x	
34 x 10.75 - 16		x	
29 x 11.0 - 10	x		
30 x 11.5 - 14.5		x	
31 x 11.50 - 16		x	
32 x 11.5 - 15	x	x	
34 x 11.75 - 14		x	
37 x 11.75 - 16		x	
34.5 x 12 - 14		x	
H31 x 13.0 - 12	x	x	
36 x 13.00 - 12		x	
37 x 13.0 - 16	x	x	
37 x 14.0 - 14	x	x	
H37 x 14.0 - 15	x	x	
C40 x 14.0 - 21	x		
H40 x 14.0 - 19		x	
H40 x 14.5 - 19	x	x	
41 x 15.0 - 18	x	x	
40 x 15.5 - 16	x	x	
40.5 x 15.5 - 16	x	x	
47 x 15.75 - 22.1		x	
H42 x 16.0 - 19	x	x	
44.5 x 16.5 - 18	x	x	
H44.5 x 16.5 - 20	x	x	
H45 x 17.0 - 20	x	x	
C40 x 18.0 - 17	x		
H46 x 18.0 - 20	x	x	
50 x 18 (-20)		x	
49 x 19.0 - 20	x	x	
H49 x 19.0 - 22	x		
50 x 20.0 - 20	x	x	
56 x 20.0 - 20	x	x	
52 x 20.5 - 20	x		
52 x 20.5 - 23	x	x	
50 x 21.0 - 20	x	x	
54 x 21.0 - 23	x		
H54 x 21.0 - 24	x		
175 x 254 x 545		x	
360 x 135 - 6		x	
380 x 150 - 4		x	
380 x 150 - 5		x	
420 x 150 (-6 1/2)		x	
450 x 190 - 5		x	
550 x 250 - 6		x	
605 x 155 - 13		x	
615 x 225 - 10		x	
640 x 170 - 14		x	
670 x 210 - 12		x	
750 x 230 - 15		x	
960 x 354 - 18		x	
30 x 8.8 R15	x		
42 x 17.0 R18		x	
1050 x 395 R16	x	x	
1400 x 530 R23	x	x	

## Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

### Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

### Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards : Monthly Additions'.

This Indian Standard has been developed from Doc : No. TED 14 ( 373 ).

#### Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

## BUREAU OF INDIAN STANDARDS

### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110 002  
Telephones : 2323 0131, 2323 3375, 2323 9402

Telegrams: Manaksanstha  
( Common to all offices )

### Regional Offices :

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg  
NEW DELHI 110 002

### Telephone

{ 2323 7617  
2323 3841

Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Kankurgachi  
KOLKATA 700 054

{ 2337 8499, 2337 8561  
2337 8626, 2337 9120

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160 022

{ 60 3843  
60 9285

Southern : C. I. T. Campus, IV Cross Road, CHENNAI 600 113

{ 2254 1216, 2254 1442  
2254 2519, 2254 2315

Western : Manakalaya, E9 MIDC, Marol, Andheri (East)  
MUMBAI 400 093

{ 2832 9295, 2832 7858  
2832 7891, 2832 7892

Branches : AHMEDABAD. BANGALORE. BHOPAL. BHUBANESHWAR. COIMBATORE.  
FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR. KANPUR.  
LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM.  
VISAKHAPATNAM.